

Code: Check.

# EVOpass<sup>®</sup> 10 Reader

Multi-technology reader with BLE option.

Proximity reader for MiFARE/DESFIRE  $^{\otimes}$  ISO14443A (13.56 MHz) cards with read/write capability, allowing access with these technologies:

- Tarjeta
- BLE
- NFC

### Secure Desfire - CSN Desfire

This reader allows for both the reading of the CNS (Chip Serial Number) on the card and the readingwritting of data in the card's memory (Secure Desfire funtion). Access to such data may be obtained through a cryptographic key for a more secure information transaction.

#### Grade 4 (depending on finish).

Certified according to EN 60839 in Access Grade 4 and EN 50131 in Intrusion Grade 4.

#### Format.

Its size allows it to be installed both in profiles and on the wall, as well as flush-mounted wherever it is needed.

#### OSDP

The reader is compatible with OSDP controllers.

Manufactured in high resistance ABS Polycarbonate.

Highly intuitive interface based on LED lights in different colours (green, red and blue). A buzzer is also included.

Available proximity technology Mifare  $\ensuremath{\mathbb{R}}$  Desfire  $\ensuremath{\mathbb{R}}$  ISO14443A (13,56 MHz) with a reading/writing capability on the card.

Recommended for both centrally operated and DOC (DORLET on card) access control installations.

Mounting on both aluminium profiles and walls, fastening with the supplied screws. Possibility of flush mounting with optional part.

Can be connected to any DORLET  $^{\mbox{\tiny (B)}}$  ASD/X controller.

Option to install both indoors and outdoors.

Need help? online@dorlet.com +34 <u>945 298 790</u>



### PHYSICAL SPECIFICATIONS

Dimensions37,6 x 94,77 x 20,18 mm.MaterialABS plasticFinishBlackSignallingLe Blue-red-green LED light and buzzer

## TECHNICAL SPECIFICATIONS

Reading mode	MIFARE <sup>®</sup> or DESFire <sup>®</sup> (EV1, EV2 y EV3)			
Reading range	Up to 4,5 cm.			
Bluetooth	Bluetooth Low Energy (BLE) v5.0			
Writting option	Yes			
Power	12 VDC.			
Maximum consumption	100 mA (12VDC).			
Operating range	From -10°C to 55°C (up to 93% humidity)			
Protection	IP67			
Connection	4 wires (+ 2 wires OSDP depending on the model) (see cable type in manual)			

### **READER - COMPARATIVE CHART**

	Desfire <sup>®</sup> (CSN)	Desfire <sup>®</sup> (memory)	OSDP	Bluetooth	Grade 4
EVOpass 10 D	X	X	Х		
EVOpass 10 D - BLE	X	X	X	x	
EVOpass 10 D - G4	X	X	Х		X
EVOpass 10 D - BLE - G4	x	X	X	х	x

The information contained in this document is subject to change without notice. Nothing contained herein shall be construed as an additional warranty. DORLET S.A.U. is not responsible for any technical or editorial errors or omissions present in this document

