

Code: Check.

EVOpass® 20 Reader

Multi-technology reader with BLE option.



Proximity reader for DESFIRE® ISO14443A (13,56 MHz) cards with reading/writting capability, enabling access with these technologies:

- Card only
- Keypad only
- BLE only
- Card and keypad
- Card and BLE

CSN (Chip Serial Number).

This reader allows for both the reading of the CSN on the card and the reading-writting of data in the card's memory.

Grade 4 (depending on finish)...

Certified according to EN 60839 in Access Grade 4 and EN 50131 in Intrusion Grade 4.

Formato.

Its format enables its instalation on a universal elecgtrical mechanism box and it is suitable for both indoor and outdoor use.

Keypad.

It can include a 12-key keypad that enables double factor identification with card and code and/or BLE sensor.

Manufactured in high resistance ABS Polycarbonate.

Highly intuitive interface based on LED lights in different colours. A buzzer is also included.

Available proximity technology Mifare® Desfire® ISO14443A (13,56 MHz) with a reading/writting capability on the card.

Recommended for both centrally operated and DOC (DORLET On Card) access control installations.

Surface-mounted on universal electrical mechanism box.

Can be connected to any DORLET® controller.

Option to install both indoors and outdoors.

PHYSICAL SPECIFICATIONS

Dimensions	81 x 101 x 31 mm.
Material	ABS plastic
Finish	Black
Keypad	Optional
Signalling	Blue-red-green LED light and buzzer

TECHNICAL SPECIFICATIONS

Reading mode	MIFARE® or DESFire® (EV1 and EV2) proximity			
Reading range	Up to 5 cm.			
Bluetooth	Bluetooth Low Energy (BLE) v5.0			
Writting option	Yes			
Power	12 VDC.			
Maximum consumption	12V/150mA.			
Operating range	From -10°C to 55°C (up to 93% humidity)			
Protection	IP65, IK04			
Connection	4 wires (see cable type in manual)			

READERS - COMPARATIVE CHART

	Desfire® (CSN)	Desfire® (memory)	Keypad	Bluetooth	Grade 4
EVOpass 20 D	X	X			
EVOpass 20 D-BLE	X	X		X	
EVOpass 20k D	X	X	X		
EVOpass 20k D-BLE	X	X	X	X	
EVOpass 20 D - G4	X				X
EVOpass 20 D BLE - G4	X			X	X
EVOpass 20k D - G4	X		X		X
EVOpass 20k D-BLE - G4	X		X	X	Х

The information contained in this document is subject to change without notice. Nothing contained herein shall be construed as an additional warranty. DORLET S.A.U. is not responsible for any technical or editorial errors or omissions present in this document.











